



(\*) VALUE FOR TYRES 215/75 R17.5  
 (\*\*) VALUE IN DEPEND OF EQUIPMENT AND TYRES

BASIC TECHNICAL PARAMETERS	
TYPE OF DRAWBAR SUSPENSION	UNSPRUNG
TYPE OF AXLE(S) SUSPENSION	MECHANICAL
TRACK [mm]	2000
WHEEL BASE [mm]	-
MAX. ALLOWED SPEED [km/h]	40
OIL REQUIREMENTS [l]	-
TYRES AND DISCS	ACCORDING TO CHART
CONNECT DIMENSION OF DISC [mm]	Ø 160 / Ø 205
NUMBERS/ DIMENSIONS WHEEL SCREWS	6/M18x1,5
TYPE OF CONNECTION DEVICE	TOWING EYE Ø 40/50
BASIC OUTSIDE DIMENSIONS	
LENGTH [mm]	5668
WIDTH [mm]	2550
HEIGHT [mm]: BASIC (*)	2220
WITH EXTENSION (*)	-
HEIGHT OF CONNECT.DEVICE ABOVE GROUND [mm] (*)	809-1029
DIMENSIONS AND PARAMETERS OF BODY FLOOR	
LENGTH [mm]	3853
WIDTH [mm]	2400
BASIC HEIGHT OF SIDES [mm]	-
HEIGHT OF EXTENSION [mm]	-
BODY VOLUME [m³]: BASIC	-
WITH EXTENSION	-
PLATE THICKNESS FLOOR/ SIDES [mm]	3
TIPP ANGLE TO BACK/ TO SIDE [°]	-
HEIGHT DURING TIPPING [mm]:	
TO BACK (WITHOUT/ WITH EXTENSION) (*)	-
TO SIDE (WITHOUT/ WITH EXTENSION) (*)	-

ALTERNATIVES OF USED TYRES				WEIGHTS	
TYRE	DISC	TYRE DIAMETER [mm]	TYRE WIDTH [mm]	SERVICE (WITH/ WITHOUT EXT.) [kg] (**)	
10.0/75-15.3	9x15.3	760	264	PAYLOAD (WITH/ WITHOUT EXT.) [kg] (**)	1600
215/75 R17.5	6.75x17.5	775	215	HIGHEST ALLOWED/ TECHNICAL PERMISSIBLE [kg]	4400
235/75 R17.5	6.75x17.5	793	240	MAX. DRAWBAR LOAD [kg]	6000
					1000

DRAWN: LANDSMAN	CONTROLLED: ING. PIKULA	TYPE NAME:	REVISION:
DATE: 27.03.2018		PU7	
PRODUCT:	UNIVERSAL TRAILERS	COMMERCIAL NAME:	PU7

