



(\*) VALUE FOR USED TRACKS  
 (\*\*) VALUE IN DEPEND OF EQUIPMENT

BASIC TECHNICAL PARAMETERS	
TYPE OF DRAWBAR SUSPENSION	UNSPUNG
TYPE OF AXLE(S) SUSPENSION	UNSPUNG
TRACK [mm]	2100/2600
WHEEL BASE [mm]	-
MAX. ALLOWED SPEED [km/h]	40
OIL REQUIREMENTS [l]	-
TYRES AND DISCS	ACCORDING TO CHART
CONNECT DIMENSION OF DISC [mm]	Ø 335/Ø 280
NUMBERS/ DIMENSIONS WHEEL SCREWS	10/M24x1,5
TYPE OF CONNECTION DEVICE	TOWING EYE Ø 50/K80

BASIC OUTSIDE DIMENSIONS	
LENGTH [mm]	9550
WIDTH [mm]	2995
HEIGHT [mm]: BASIC (*)	-
WITH EXTENSION (*)	3892
HEIGHT OF CONNECT.DEVICE ABOVE GROUND [mm] (*)	541

DIMENSIONS AND PARAMETERS OF BODY FLOOR	
LENGTH [mm]	6694
WIDTH [mm]	2964
BASIC HEIGHT OF SIDES [mm]	-
HEIGHT OF EXTENSION [mm]	-
BODY VOLUME [m³]: BASIC	30
WITH EXTENSION	-
PLATE THICKNESS FLOOR/ SIDES [mm]	-
TIPP ANGLE TO BACK/ TO SIDE [°]	-
HEIGHT DURING TIPPING [mm]:	
TO BACK (WITHOUT/ WITH EXTENSION) (*)	-
TO SIDE (WITHOUT/ WITH EXTENSION) (*)	-

WEIGHTS	
SERVICE (WITH/ WITHOUT EXT.) [kg] (**)	7500
PAYLOAD (WITH/ WITHOUT EXT.) [kg] (**)	4500/22500
HIGHEST ALLOWED/ TECHNICAL PERMISSIBLE [kg]	12000/30000
MAX. DRAWBAR LOAD [kg]	3000

DRAWN: ING. MOLVA	CONTROLLED: ING. PIKULA	TYPE NAME:	NP30	REVISION:
DATE: 13.03.2018				
PRODUCT: GRAIN CART		COMMERCIAL NAME:	GIGANT	